

Network Systems ► Wall-Mounted Distributor ► ODB/48 Wall-Mounted Distributor New



General Information

The ODB/48-IP65 is an easy-to-handle and universally usable wall-mounted distributor for indoor and outdoor application holding up to 48 Simplex adapters or Duplex adapters with optical connectors and up to 96 splices in splice cassettes.

Furthermore it is also possible to integrate optical couplers, filters and other components into the enclosure in line with the requirements of the specific application. The splice storage area is separately protected. The patching and splicing areas with the loose buffer fibre storage have been separated, in order to minimize disruptions of the spliced installation when changing patched connections. The secure entry of cables is ensured via metric threaded glands on the bottom side.

Features

- Wall-mounted distributor for indoor/outdoor applications
- Robust enclosure consisting of: chassis, cover with holder for up to 48 adapters / 96 connectors, separate splice tray (max. 144 splice connections)
- Adapter plate for up to 48 LSH, SC and LC (duplex) adapters (other connector types on request)
- Separate, protected storage of splices and patch cords

- Holds up to 4 standard splice cassettes and/or 4 BG10 optical coupler cassettes
- Cable entry via individually usable rubber gasket or metric threaded glands (on request)
- Available also with installed lead-in connectors and pigtails, ready for splicing (on request)

Dimensions

- 350 x 334 x 110 mm

Weight

- 4.3 kg

Material

- PVC/ABS

Colour

- RAL 9003

IP Rating

- IP 65

Fire Behaviour

- V0/UL94

Dimensions

